

#### Service Intended

Suitable for measuring low pressure / vacuum in gaseous, non-aggressive dry media that does not attack copper alloy or stainless steel parts or will obstruct the pressure system. Typical applications will be in the medical, laboratory, vacuum and filter monitoring industry.

#### **Case Details**

Nominal Dia: 63, 80, 100, 160mm Material: Stainless steel 304

#### Bezel

Sizes 63, 80 & 100mm Roll ring type - tamper proof. Size 160mm Bayonet locking, twist type - removable. Material: Stainless steel 304

## **Pressure Connections**

Material: Type 3: Brass. Type 4: Stainless steel 316 Sizes: 63, 80mm nom. dia: 1/8" & 1/4" in BSP or NPT Sizes: 100, 160mm nom. dia: 1/4", 3/8" & 1/2" in BSP or NPT (Position: See "Mounting Configurations".)

#### **Mounting Flange**

Material: Polished stainless steel 304 (Position: See "Mounting Configurations".)

## **Pressure Element - Capsule**

Material: Type 3: Cu-alloy.

Type 4: Stainless steel 316.

#### **Pressure Ranges**

0 to 2.5...40 kPa pressure or vacuum (see standard pressure ranges)

#### **Geared Movement**

Material: Clockwork brass or stainless steel.

Special feature: External zero adjustable from the front.

#### **Pointer**

Collet: Aluminium or brass Blade: Black aluminium

Material: Aluminium, white with black lettering.

#### Window

Plexiglass / polycarbonate.

## **Weather Protection**

**IP 54** 

#### **Working Pressure**

Steady: Full scale value Fluctuating: 90% of full scale value For pulsating pressure, the use of an inlet restrictor is recommended.

## **Accuracy Class**

63mm & 80mm dia: Class 2.5 100mm & 160mm dia: Class 1.6

# **Operating Temperature**

Ambient: -20 °C to + 60 °C Medium: +70 °C

## **Optional Extras**

Calibration Certificate Customized scale plates (customer logo, red line, etc) Special Dials, other than standard (dual scale, bar, psi) Colour Coding of dial Blow out disc

## PRESSURE MEASUREMENT

## Capsule Gauge - Low Pressure

Type R3: Stainless steel case with brass capsule


Type R4: Stainless steel case with stainless steel capsule

Data Sheet P CAP3-4



For dimensional drawing see technical section

## **MOUNTING CONFIGURATIONS**



- A: Bottom connection, no flange
- B: Rear connection, no flange
- C: Bottom connection, front flange D: Rear connection, front flange
- E: Bottom connection, rear flange F: Rear connection, rear flange
- Y: Rear con. narrow front ring (clamp mtg)
- STANDARD PRESSURE RANGES Figure Interval Minor Graduations Figure Interval Minor Graduations Ranges Ranges Pressure Pressure 0/2.5 kPa 0.5 0.05 0/25 mbar 0.5 0/4 kPa 0.1 0/40 mbar 10 0.1 0/60 mbar 10 0/10 kPa 0.2 0/100 mbar 20 0/16 kPa 0.2 0/160 mbar 20 0/250 mbar 50 0/40 kPa 10 1 0/400 mbar 100 10 Vacuum Vacuum 25/0 mbar 2.5/0 kPa 0.05 0.5 4/0 kPa 0.1 40/0 mbar 6/0 kPa 0.1 60/0 mbar 10 10/0 kPa 0.2 100/0 mbar 16/0 kPa 0.2 160/0 mbar 20 25/0 kPa 250/0 mbar

# **HOW TO ORDER USING OUR PART NUMBERS**

astornizea ana otner	<del>Julius Juliu</del>	<del>ao bai 7 p</del> i	) / II I	700	to. are	ava	nabio o	<del>11 10quost</del>	
		- P	-2	Δ.	100	_ D	1/2 B	10 kPa	
		11	0	$\sim$	100		1/2 0	10 Ki a	
Casing Type:			- 1		- 1	- 1		- 1	
odding Type			- 1	- 1	- 1				
o =			- 1	- 1	- 1				
Gauge Type:				- 1	- 1				
				- 1	- 1				
Configuration:					- 1				
					- 1				
Dial Size:					_				
_									
Dry:						- 1			
Connection Size: -									
0011110011011 01201								- 1	
D								- 1	